

VETROSPACE S

ROOM FOR 2

This compact meeting pod doubles as a personal space for video conferences, phone calls, or private corridor discussions. You can design and furnish it according to your needs from a variety of options.



[VIEW ONLINE →](#)



Plug-and-play solutions



Automated, smart CO2-controlled ventilation



Best-in-class soundproofing



Easy access for people with mobility limitations



Advanced two-stage air filtration (coarse and HEPA 13)



Antimicrobial LED lighting



Antimicrobial surface nanocoating



ISO 7 indoor air quality performance



TECHNICAL SPECS

Exterior dimensions	W210 / D110 / H240 cm W82.7 / D43.3 / H94.5 in
Exterior material	LP-laminate
Interior dimensions	W200 / D100 / H220 cm W78.7 / D39.4 / H86.6 in
Interior material	Acoustic ECOfelt lining
Weight	760 kg 1670 lbs
Indoor surface area	2 m ² 21.4 ft ²
Installation height requirement	>250 cm >98.5 in
Fire safety	UL 723: Class A-C (surface) ASTM E648: Class 1 (flooring)
Electrical safety	IEC 60335-1:2020 UL 962 (E514776)
Seismic safety	Special SEISMIC Certification (2019-0176-COC-01-00), International Building Code (IBC) 2018 (23.02.2021), California Building Code (CBC) 2019 (23.02.2021)
Door	Patented sliding door
Glass thickness	16.7 mm 0.66 in sound-control safety glass
Sound reduction	Ds: 30.6 dB (ISO 23351-1) 43-46dB Rw Lab STI: 0.05
Ventilation system	Advanced two-stage air filtration (coarse and HEPA 13)
Air flow	Max. 40 l/s
Pressure	Positive air pressure
Lighting	VLD antimicrobial LED
Power supply	110-240 VAC / 16 A / 50-60 Hz
Power	50 W average, 150 W maximum
Power sockets	4 as standard

