

# VETROSPACE XS

## GREAT FOR 1

Our smallest pod doesn't compromise on comfort or convenience. It's ideal as an office phone booth for private, distraction-free conference calls and is quick to install and easy to move thanks to the wheels.

[VIEW ONLINE →](#)



Plug-and-play solutions



Built-in wheels for easy relocation



Best-in-class soundproofing



Excellent ventilation for fresh air



Antimicrobial LED lighting



Antimicrobial surface nanocoating



## TECHNICAL SPECS

<b>Exterior dimensions</b>	W110 / D110 / H225 cm   W43.3 / D43.3 / H88.6 in
<b>Exterior material</b>	LP-laminate
<b>Interior dimensions</b>	W80 / D100 / H207.5 cm   W31.4 / D39.4 / H81.7 in
<b>Interior material</b>	Acoustic ECOfelt lining
<b>Weight</b>	420 kg   710 lbs
<b>Indoor surface area</b>	~ 1 m <sup>2</sup>   10.7 ft <sup>2</sup>
<b>Modular sizes</b>	1-100 m <sup>2</sup>
<b>Installation height requirement</b>	>225 cm   >88.6 in
<b>Fire safety</b>	UL 723: Class A-C (surface) ASTM E648: Class 1 (flooring)
<b>Electrical safety</b>	IEC 60335-1:2020 UL 962 (E514776)
<b>Seismic safety</b>	Special SEISMIC Certification (2019-0176-COC-01-00), International Building Code (IBC) 2018 (23.02.2021), California Building Code (CBC) 2019 (23.02.2021)
<b>Patents</b>	US PATENT: 11.492.815 B2 International patents (FI, US, EP, CH, HK, RU)
<b>Door</b>	Hinged door
<b>Glass thickness</b>	11 mm   0.43 in sound-control safety glass
<b>Sound reduction</b>	STI: 0.05 – Ds: Class A (ISO 23351-1)
<b>Ventilation system</b>	Basic single state coarse air filtering
<b>Air flow</b>	20 l/s
<b>Pressure</b>	Positive air pressure
<b>Lighting</b>	VLD antimicrobial LED
<b>Surface treatment</b>	Photocatalytic antimicrobial nanocoating
<b>Power supply</b>	110-240 VAC / 16 A / 50-60 Hz
<b>Power</b>	50 W average, 150 W maximum
<b>Power sockets</b>	1 as default, Integrated USB-charging ports

